

## **ANNUAL MAINTENANCE CHECKLIST**

(Copy this section as needed and maintain for your records or visit www.playstarinc.com/maintenance)

t the beginning of play season: Date:	Twice a month during play season: Date:
Tighten all hardware.	☐ Tighten all hardware.
Lubricate all metallic moving parts per manufacturer's instructions.	Check all protective coverings on bolts, pipes, edges, and corners. Replace if they are loose, cracked, or missing
Check all protective coverings on bolts, pipes, edges, and corners. Replace if they are loose, cracked, or missing.	☐ Rake and check depth of loose fill protective surfacing materials to prevent compaction and to
Check all moving parts including swing seats, ropes,	maintain appropriate depth. Replace as necessary.
cables, and chains for wear, rust, or other	Once a month during play season: Date:
deterioration. Replace as needed.	Lubricate all metallic moving parts per
Check metal parts for rust. If found, sand and repaint	manufacturer's instructions.
using a nonlead-based paint meeting the requirements of 16 CRF 1303.	☐ Check all moving parts including swing seats, ropes,
☐ Check all wood members for deterioration and	cables, and chains for wear, rust, or other deterioration. Replace as needed.
splinters. Sand down splinters and replace	
deteriorating wood members.	At the end of each play season or when the temperature drops below 0° F: Date:
Reinstall any plastic parts, such as swing seats or	
any other items that were removed for the cold season.	Remove plastic swing seats and other items as specified by the manufacturer and take indoors or do not use.
Rake and check depth of loose fill protective	Rake and check depth of loose fill protective
surfacing materials to prevent compaction and to maintain appropriate depth. Replace as necessary.	surfacing materials to prevent compaction and to
mamam appropriate depth. Heplace as necessary.	maintain appropriate depth. Replace as necessary.

If any of these conditions exist, call 1-888-752-9782 for ordering information. Clean plastic components with warm water and a mild detergent such as dish soap.